I-LINE by Burkhard Dämmer

Short Suspension - LED ζ

SIZE



REFERENCES

I-LN S 120 BK LED DIMO-10V UL
I-LN S 120 BK LED DIMTRIAC UL
I-LN S 120 WH LED DIMO-10V UL
I-LN S 120 WH LED DIMTRIAC UL



COMPONENTS

Wood Veneer Shade

Matte Satin Acrylic Bottom Diffuser

Lacquered Metal Upper Cover Plate

Matte Black Metal Canopy: 24 x 1.6 x 2,6" - disc Ø4.5"

2 Black Electrified Cables: 98"

LIGHT SOURCE



120 - 277V: Dimmable LED 0-10V or Dimmable LED TRIAC

Driver: 1 x Constant Voltage 24V **Integrated LED**: 1 x 1.15 m Strip 24 W/m 2.700K, CRI>90, 30 W, 50-60Hz, 1.725 lm*

LED Position in Fixture



*Measurements obtained by photometric laboratory tests using ivory white shades. Veneer Ref: 20 Ivory White.

PACKAGING

Box Size: 54 x 8 x 9" **Box Volume**: 2.47 ft³

Weight: Gross - 16.5 Lb | Net - 9.7 Lb

SELECT FROM FOLLOWING

DIMMING SYSTEM

LED 0-10V or TRIAC

LIGHT SOURCE TEMPERATURE

Available 2.700K. 3.000K or 4.000K

WOOD VENEER FINISHES

20 - Ivory White

21 - Natural Cherry

24 - Yellow

25 - Orange

26 - Red

28 - Blue

CANOPY FINISHES

■ BK - Matte Black

33 - Pale Rose

34 - Sea Blue

29 - Grev

22 - Natural Beech

34 - Sea Blue

WH - Matte White