
by Ray Power

SIZE



REFERENCES

LOLA SG BK LED DIMO-10V UL LOLA SG BK LED DIMTRIAC UL LOLA SG WH LED DIMO-10V UL LOLA SG WH LED DIMTRAIC UL LOLA SG NI LED DIMO-10V UL LOLA SG NI LED DIMTRIAC UL



COMPONENTS

Wood Veneer Shade

Transparent Acrylic Frame

Metal Canopy: ø6,7"

Electrical Cable: 98"

LIGHT SOURCE



120 - 277V: Dimmable LED 0-10V & Dimmable LED TRIAC

Driver: Constant Current 1.400 mA Integrated LED: Led Strip 2.700K, CRI>90, 52 W, 50-60Hz, 2.860 lm*

*Measurements obtained by theoretical calculations at LZF using ivory white shades. Veneer Ref: 20 Ivory White.

SELECT FROM FOLLOWING

DIMMING SYSTEM

LED 0-10V or TRIAC

LIGHT SOURCE TEMPERATURE

Available 2.700K. 3.000K or 4.000K

WOOD VENEER FINISHES

20 - Ivory White

22 - Natural Beech

CANOPY & CABLE FINISHES

BK - Matte Black / Black Cable

WH - Matte White / White Cable

NI - Matte Nickel / Transparent Cable

PACKAGING

Box Size: 40 × 40 × 24" Box Volume: 22.3 ft³

Weight: Gross - 39.2 Lb | Net - 15.2 Lb